



MODEL	X	X/T	BRACKETS	X	X/T	BRACKETS	X	X/T	BRACKETS	X	X/T	BRACKETS	G	E	F
0201....15	77-150	X/4	2	152-225	X/6	3	227-300	X/8	4	302-375	X/10	5	14.5	13.5	29.5
0201....25	102-200	X/4	2	202-300	X/6	3	302-400	X/8	4	402-500	X/10	5	17.5	20.5	37.5
0201....40	132-260	X/4	2	262-390	X/6	3	392-520	X/8	4	522-600	X/10	5	22	30	48
0201....50	152-300	X/4	2	302-450	X/6	3	452-600	X/8	4	/	X/10	5	26	36	65
0201....65	182-360	X/4	2	362-540	X/6	3	542-600	X/8	4	/	X/10	5	32	44	80
0201....75	202-400	X/4	2	402-600	X/6	3	/	X/8	4	/	X/10	5	35	55	90
0201....100	241-480	X/4	2	482-600	X/6	3	/	X/8	4	/	X/10	5	45	64	104

	0201....15	0201....25	0201....40	0201....50	0201....65	0201....75	0201....100
SPESSORE LAMIERA / METAL SHEET THICKNESS / DICKE DES BLECHS	0.5-0.9	0.9-1.7	1.7-2.8	2.8-3.8	3.8-4.9	4.9-6.0	6.0-8.0
(X) LUNGHEZZE / LENGTHS / LÄNGEN MIN-MAX	30-375	40-500	40-600	50-600	50-600	50-600	60-600
(D) DIAMETRO ROTANTE / ROTATING DIAMETER / Ø BIEGEEINSATZ	15	25	40	50	65	75	100
(SW) LARGHEZZA CORPO / BODY WIDTH / BREITE DES GRUNDKÖRPERS	54	73	98	123	148	175	196
(SF) DIST. MIN. ROTANTE-FRONT / DIST. MIN. ROTATING BODY-FRONT PART / ABSTAND MIN. DREHKÖRPER	19	28	40	47	56	70	78
(SK) DIST. ROTANTE-CHIAVETTA / DIST. ROTATING BODY - WEDGE / ABSTAND DREHKÖRPER	35	45	58	76	92	105	118
(SH) DIST. ROTANTE-BASE - DIST. BODY-ROTATING BODY / ABSTAND DREHKÖRPER-GRUNDKÖRPER	22	35	48	60	73	86	96
(GL) LARGHEZZA SUPPORTO / SUPPORT WIDTH / BREITE HALTER	28.6	38.1	50.8	63.5	76.2	88.9	116
(L) INGOMBRO SUPPORTO / HOLDER OVERALL / HÖHE HALTER	5.4	8.2	12	16.35	20	24	30
(M) INGOMBRO / HOLDER / HALTER	7.9	12.4	19.9	24.8	31.6	38	49.7
(H) DIAMETRI FISSAGGI / DIAMETERS OF THE FIXING / BEFESTIGUNGSDURCHMESSER	M5	M8	M10	M10	M12	M12	M16
(E) POSIZIONE DEI FISSAGGI / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	13.5	20.5	30	36	44	55	64
(F) POSIZIONE DEI FISSAGGI / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	29.5	37.5	48	65	80	90	104
(G) POSIZIONE DEI FISSAGGI / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	14.5	17.5	22	26	32	35	45

Può lavorare anche senza lubrificazione / It works also without lubrication / Es funktioniert auch ohne Schmierung / Il peut fonctionner sans lubrification

MODELLO D'ORDINE / ORDER EXAMPLE / BESTELLBEISPIEL / MODÈLE DE COMMANDE

MODEL **0201** TYPE BEND **03** Ø DIAMETER **Ø50** LENGHT **500** ANGLE **90°**