



MODEL	X	G	GL	X/T	BRACKET	X	G	GL	X/T	BRACKET	X	G	GL	X/T	BRACKET	X	G	GL	X/T	BRACKET	X	G	GL	X/T	BRACKET
0204....15	77-105	13.5	16	X/4	2	106-160	20	28.6	X/4	2	162-225	20	28.6	X/6	3	227-300	20	28.6	X/8	4	302-375	20	28.6	X/10	5
0204....25	102-138	18	22	X/4	2	139-210	26.5	38.1	X/4	2	212-300	26.5	38.1	X/6	3	302-400	26.5	38.1	X/8	4	402-500	26.5	38.1	X/10	5
0204....40	132-178	23.5	30	X/4	2	180-270	35	50.8	X/4	2	272-390	35	50.8	X/6	3	392-520	35	50.8	X/8	4	522-600	35	50.8	X/10	5
0204....50	152-218	27	34	X/4	2	220-320	42	63.5	X/4	2	322-450	42	63.5	X/6	3	452-600	42	63.5	X/8	4	/	/	/	X/10	5
0204....65	202-270	36	46	X/4	2	272-400	52	76.2	X/4	2	402-550	52	76.2	X/6	3	552-600	52	76.2	X/8	4	/	/	/	X/10	5
0204....75	212-298	38	49	X/4	2	300-450	58	88.9	X/4	2	452-600	58	88.9	X/6	3	/	/	/	X/8	4	/	/	/	X/10	5
0204....100	260-378	47.5	61	X/4	2	380-550	75	116	X/4	2	552-600	75	116	X/6	3	/	/	/	X/8	5	/	/	/	X/10	5

	0204....15	0204....25	0204....40	0204....50	0204....65	0204....75	0204....100
SPESORE LAMIERA / METAL SHEET THICKNESS / DICKE DES BLECHS	0.5-0.9	0.9-1.7	1.7-2.8	2.8-3.8	3.8-4.9	4.9-6.0	6.0-8.0
LUNGHEZZE / LENGTHS / LÄNGEN MIN-MAX (X)	40-375	51-500	66-600	75-600	100-600	105-600	130-600
DIAMETRO ROTANTE / ROTATING DIAMETER / Ø BIEGEEINSATZ (D)	15	25	40	50	65	75	100
LARGHEZZA CORPO / BODY WIDTH / BREITE DES GRUNDKÖRPERS (SW)	44	59	84	106	131	149	178
DIST. MIN. ROTANTE-FRONT / DIST. MIN. ROTATING BODY-FRONT PART / ABSTAND MIN. DREHKÖRPER (SF)	9	14	26	30	39	44	60
DIST. ROTANTE-CHIAVETTA / DIST. ROTATING BODY - WEDGE / ABSTAND DREHKÖRPER (SK)	35	45	58	76	92	105	118
DIST. ROTANTE-BASE (SH) - DIST. BODY-ROTATING BODY / ABSTAND DREHKÖRPER-GRUNDKÖRPER	22	35	48	60	73	86	96
LARGHEZZA SUPPORTO (GL) / SUPPORT WIDTH / BREITE HALTER	28.6	38.1	50.8	63.5	76.2	88.9	116
INGOMBRO SUPPORTO (L) / HOLDER OVERALL / HÖHE HALTER	5.4	8.2	12	16.35	20	24	30
INGOMBRO (M) / HOLDER / HALTER	7.9	12.4	19.9	24.8	31.6	38	49.7
DIAMETRI FISSAGGI (H) / DIAMETERS OF THE FIXING / BEFESTIGUNGSDURCHMESSER	M6	M8	M10	M12	M16	M16	M20
POSIZIONE DEI FISSAGGI (E) / POSITION OF THE FIXING / BEFESTIGUNGSPPOSITION	16	23	33	41	52	58	71

Può lavorare anche senza lubrificazione / It works also without lubrication / Es funktioniert auch ohne Schmierung / Il peut fonctionner sans lubrification

MODELLO D'ORDINE / ORDER EXAMPLE / BESTELLBEISPIEL / MODÈLE DE COMMANDE

MODEL **0204** TYPE BEND **03** Ø DIAMETER **Ø50** LENGTH **500** ANGLE **90°**